




# Gridded Surface Subsurface Hydrologic Analysis





# What is GSSHA?

- GSSHA is a complete watershed simulation and management model used for hydrologic, hydraulic, sediment and quality simulation and management.
- GSSHA is a fully distributed, physics based model that utilizes a grid to represent the watershed.
- GSSHA is a product of the US Army ERDC
  - Maintained
  - Supported
  - Distributed
- GSSHA is a direct descendent of the surface water hydrologic model CASC2D developed at Colorado State University.
- The original version of GSSHA is the result of my dissertation work at University of Connecticut.




Downer, C. W. *Identification and Modeling of Important Stream Flow Producing Processes in Watersheds*, PhD Dissertation, University of Connecticut, 2002.




# How does GSSHA Work?

- GSSHA works on a uniform spatial grid.
- Basic equations of mass, energy, and momentum conservation are solved with finite volume and finite difference techniques.
- Point processes are solved at the grid level.
- Point responses are integrated to get the system response.

## Computational Grid




Cascading planes  
in two dimensions –  
CASC2D





# Why Does This Matter?

- Spatial variability.
- Physically based parameters.








# Spatial Variability

- Explicitly include spatially heterogeneous features, such as varying land use, source areas, BMPs, etc.





# Physically Based Parameters

- Values are based on physical conditions in the computational element.
  - requires less calibration data
  - extendible beyond calibration range
- The tie to physical conditions provides a means to logically alter parameters based on changing conditions.
  - land use changes
  - project alternatives
  - climate change






# What GSSHA Can Do?




Surface water hydrology




Surface Water/Groundwater Interaction




Surface water quality and TMDL's



Sediment Management



Contaminant fate/transport in surface water and groundwater and related health risk assessment




## Watershed Modeling and Management







# Watershed Modeling Components






# 2D Overland Flow

$$\frac{\partial h}{\partial t} = \frac{\partial \bar{q}}{\partial x} + \frac{\partial \bar{q}}{\partial y}$$

$$\bar{q} = \frac{1}{n} d^{5/3} S_{fx}^{1/2} \vec{i} + \frac{1}{n} d^{5/3} S_{fy}^{1/2} \vec{j}$$

$$S_{fx} = S_{ox} - \frac{dh}{dx}; S_{fy} = S_{oy} - \frac{dh}{dy}$$








# 1D Stream Network

$$Q_{i-1/2} = \frac{1}{n} A_{i-1} R_{i-1}^{2/3} S_{f_{i-1/2}}^{1/2}$$

$$\frac{\partial h}{\partial x} = S_o - S_f$$

$$\frac{\partial A}{\partial t} + \frac{\partial Q}{\partial x} = S$$





# Infiltration and Evapotranspiration

- Infiltration
  - Richards Equation
    - 3 primary soil layers
    - infinite subdivisions of each layer
  - Green and Ampt, 1 layer
  - Two-layer Green and Ampt w/ Soil Moisture Redistribution
  - Three-layer Green and Ampt model with soil moisture accounting
- Evapotranspiration
  - Deardorff bare earth
  - Penman – Montieith









# Continuous Simulations

- GSSHA has the capability to perform continuous simulations for unlimited periods of time.
  - Soil moisture modeling between events.
  - Model provides the initial conditions for each episodic event.
  - This is critical for determining verifiable parameter sets (Senarath et. al, 2000).






# Spatially Explicit Soil Moisture Evolution





# Snow Accumulation and Melt

- Modeling of Snow Water Equivalent (SWE)
  - Three Snow Accumulation / Melt Methods
    - Energy Balance Method
    - Temperature-Index Method
    - Hybrid Energy Balance Method
  - Accounting for Snow Pack Dynamics
- Adjustments to HMET Forcing Data
- Melt Water Transport
  - Vertical Flow through Snow Pack
  - Lateral Flow through Snow Pack
  - Frozen Ground to Impede Infiltration





# Snow Accumulation and Melt





# 1D Stream Features

- Can be added to your 1D stream network
- Types
  - Broad crested weirs
    - Horizontal
    - Parabolic
  - Culverts
    - Circular
    - Rectangular
  - Active control structures
    - Rule curve
    - Scheduled discharge
  - Generic structure rating curve
- Reservoirs or detention basins can also be added to your network.







# 2D Groundwater

$$\frac{\partial}{\partial x} \left( K_{xx} b \frac{\partial E_{ws}}{\partial x} \right) + \frac{\partial}{\partial y} \left( K_{yy} b \frac{\partial E_{ws}}{\partial y} \right) = S \frac{\partial E_{ws}}{\partial t} + W(x, y, t)$$

- Single-layer free surface groundwater equation
- Provides recharge -> groundwater flow  
-> stream, seep interaction
- Allows for environmentally important flows (low flows, wetlands) to be modeled
- Important for modeling saturation excess runoff





# Surface Water Groundwater Interaction

- Surface water models can only represent the fast response of the watershed, runoff due to infiltration excess (with deep depth-to-groundwater).
- Groundwater models can only represent the slow response of the watershed, due to stream graining and losing from/to groundwater.
- Shallow depth-to-groundwater is needed for saturation excess runoff
- All responses are required to simulate watershed responses in complex watersheds with mixed runoff.
- GSSHA is specifically formulated to solve this complex problem.










# Storm and Tile Drains

- Connected set of pipes, manholes, inlet grates
- Tile drains are porous pipes that drain groundwater in agricultural areas.







# Sediment Transport

- Event based erosion and deposition model (not USLE-based)
  - Overland
  - Streams
- User-defined sediment properties

Erosion/Deposition


■	Low/Low
■	Low/High
■	High/Low
■	High/High





# Constituent Transport

- GSSHA has the capability to simulate constituent fate and transport in surface water components of the model.
  - Soil column
  - Overland
  - Streams
- Kinetics
  - First order
- Dissolved and sorbed phases





# How Do I Build a GSSHA Model?

- GSSHA models are most easily built using the WMS software.
- Some files must be built with common text editors or spreadsheets. Additional utilities for building file types not supported by WMS are provided on the GSSHA wiki.
- Once the spatial aspects of the model have been assigned, simple changes to model input may be accomplished by directly editing the project and mapping table files.







# How Do I Run GSSHA?

- GSSHA is run from the command line in a Windows Dialogue box.
- GSSHA can also be run from WMS, which basically calls up a Windows Dialogue box and launches GSSHA for you.
- GSSHA models work on the following platforms:
  - Windows
  - LINUX
  - Supercomputer





# Why use GSSHA?

- Model floods, water balance, and ecological flows
  - Flexible processes selection tailored to watershed and project characteristics
- Integrated Process Modeling
  - Changes in one process affect other processes
  - Coupled groundwater, soil moisture, stream, and overland flow models
- Spatially explicit formulation: can evaluate impacts of *where* changes occur
  - Location of wetlands addition
  - Location of land use change
- Physical Process-driven model: can simulate fundamental changes in processes such as
  - tile drain removal,
  - addition of wetlands, and
  - changes in land use





# Why use GSSHA?

## Integrated Surface and Overland Modeling

- Stream channels are integrated with the overland and groundwater flow regimes.
- Allows water in 2D systems to enter/exit the stream channel at correct time and location.
- Reservoirs are simulated as both channel and overland features. Reservoirs can expand and contract in both the channels and on the overland flow plane.
- *Each physically simulated processes is allowed to interact with and be affected by the other physical processes. This allows for impacts and changes to be more realistically modeled.*







# Dynamic Reservoir Simulation







# Why use GSSHA?

## Explicit Spatial Process Descriptions

- Spatially varied heterogeneity
- Explicitly resolve features in the grid
  - Land use
  - Soil type
  - Depressions
  - BMPs
  - Roads
  - Wetlands
- Track fate of water, sediment, contaminants along flow path
  - Infiltration along path
  - Settling/erosion along path
  - Reactions along path





## Modeling changes in physical processes


- Converting from tile drained fields to wetlands is a change in the fundamental runoff mechanisms
- GSSHA simulates the actual runoff processes in their spatial context
- By simulating the physical processes we are able to model changes to the watershed that include
  - Precipitation events outside the calibration range
  - Changes in fundamental runoff generation mechanisms
  - Changes in runoff transport mechanisms
  - Resulting impacts to nutrient and sediment production and transport






# Urbanization and Wetlands Creation in the Kishwaukee Watershed

LAND COVER IN THE KISHWAUKEE RIVER BASIN



18








# Watershed Overview

- Watershed Area:  
~1100 mi<sup>2</sup>
- Stream Miles:  
~1000 mi
- Overland flow
- Stream flow
- Infiltration
- Groundwater
- Tile Drains
- Detention Basin
- Wetland Hydraulics





# Project Goals


- Develop Watershed Management Plan
  - Placement of 1600 ac of wetlands
  - Removal of tile drains
  - Assess impacts of future land use







# Impacts of Spatial Location: Wetlands Location Study








# Wetlands Location Results



## Belvidere, IL







# Spatial Hydrology: Dealing with Runoff Processes Changes

- Spatial effects of land use changes
  - *Where* you put a commercial zone, detention basin, or wetland changes the hydrology
  - Include engineered wetlands
  - Include detention basins
  - Planning and after-the-fact land use changes






# Urbanization: Kishwaukee Watershed








# Central Kishwaukee Flooding





# Urbanization: Kishwaukee Watershed Results







# Simulation of Inland Flooding Effects




- On Saturday Oct. 27, 2012, ERDC CHL was asked by the New York District (NAN) through the UROC to provide estimates to potential flooding in the New York City area before 1200 EDT on Monday October, 29, 2012.
- Provide potential coastal storm surge estimates using the hydrodynamic model **ADCIRC**
- Provide potential inland flooding estimates using the overland flow model **GSSHA**



# ADCIRC Coastal Circulation and Storm Surge Model



- An unstructured finite element hydrodynamics model
- 2D and 3D simulations
- Wetting/Drying algorithm allows for storm surge inundation over previously dry land
- Highly portable code
- A part of ERDC's Coastal Storm Modeling System



## Surge Modeling for Sandy



- Used two meshes
  - EC2001FIMP Grid
  - FEMA Region 2 Grid
- Used tidal forcing and the imbedded asymmetric vortex Holland wind/pressure model
- Wind model inputs derived from the NHC forecast using the ASGS in collaboration with Dr. Jason Fleming and Dr. Rick Luettich
- Advisories 22 – 31 were simulated
- Advisory 26 results sent to NAN.





# GSSHA New York Models

- GSSHA is a gridded, physics-based full hydrology model
  - Overland flow, stream flow, groundwater, vadose zone, storm and tile drains, wetlands, erosion, constituent transport
- GSSHA 2D Overland Flow Model used to predict inland flood inundation
  - Use time-varying specified head condition for storm surge
- 2 Models:
  - Central NY Model @75m (right)
  - Long Island Model @150m
- Rainfall estimated from NWS plots
- Storm surge from ADCIRC







# Coastal Flood Modeling – Hurricane Sandy







# Summary

- GSSHA is fully distributed, physics based watershed analysis and management tool.
- It can and has been used for a variety of analysis and engineering studies.
- The spatially explicit nature of the model allows user to directly incorporate important project features into the model.
- The physical basis allows parameter values to be logically adjusted for changing conditions – land use, BMPs, climate conditions.
- The spatially explicit physics based approach offers advantages over simply models for analysis of conditions outside the range of calibration, changing, and inherently distributed processes such as sediment transport and non-point source pollution.





# New Orleans

